



(19)

(11) Publication number:

**07301113 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **06116067**(51) Int'l. Cl.: **F01N 3/02 F01N 3/02 B01D 46/00 B01D  
53/34**(22) Application date: **06.05.94**

(30) Priority:

(43) Date of application      **14.11.95**  
publication:(84) Designated contracting  
states:(71) Applicant: **ISUZU CERAMICS****KENKYUSHO:KK**(72) Inventor: **SUZUKI SHOGO**

(74) Representative:

## (54) SEAL MATERIAL USED FOR DPF AND MANUFACTURE THEREOF

(57) Abstract:

PURPOSE: To provide a seal material used for diesel particulate filter(DPF) having a high strength and abundant sealing properties and to provide manufacture thereof.

CONSTITUTION: A seal material 3 is prepared in such a manner that a mixture consisting of 80wt.% ceramics powder and 20wt.% inorganic fibers is added with low melt point borosilicate glass in the same amount as that of the mixture and kneaded to produce a clay-form substance. After a molded product molded by using the clay-form substance is dried, the molded product is baked at 900°C for two hours. The seal material is arranged in a case 2 incorporated in the middle of the exhaust passage 1 of a diesel engine. The seal material is used for sealing the vicinity of a filter therewith so that exhaust gas flows to a filter 4 to collect particulate contained in exhaust gas.

COPYRIGHT: (C)1995,JPO

